

Tabelle zur Bestimmung der Gewindeabmessung

DIN ISO 228 / BSP

| Gewinde- Nennweite | Aussengewinde- Durchmesser mm | Innengewinde- Durchmesser mm |
|-----------------------|-------------------------------------|------------------------------------|
| 1/4" | 13,16 | 11,5 |
| 3/8" | 16,66 | 15,0 |
| 1/2" | 20,96 | 18,7 |
| 3/4" | 26,44 | 24,2 |
| 7/8" | 30,20 | 27,9 |
| 1" | 33,25 | 30,3 |
| 1 1/8" | 37,90 | 35,0 |
| 1 1/4" | 41,91 | 39,0 |
| 1 3/8" | 44,33 | 41,4 |
| 1 1/2" | 47,81 | 44,9 |
| 1 3/4" | 53,75 | 50,8 |
| 2" | 59,62 | 56,7 |
| 2 1/4" | 65,71 | 62,8 |
| 2 3/8" | 69,00 | 66,7 |
| 2 1/2" | 75,19 | 72,3 |
| 2 3/4" | 81,54 | 78,6 |
| 3" | 87,84 | 85,0 |
| 3 1/4" | 93,98 | 91,1 |
| 3 1/2" | 100,33 | 97,4 |
| 3 3/4" | 106,68 | 103,8 |
| 4" | 113,03 | 110,1 |
| 4 1/2" | 125,73 | 122,8 |
| 5" | 138,43 | 135,5 |